

SPREAD RATE CHARTS

V – Bond™

Application	Trowel Size	Trowel Type	Coverage* (Per Gallon)
VERDEX® to sub-floor	3/32" x 3/32" x 3/32"	V-Notch	100 Sq. Ft.
1/4" Engineered wood to VERDEX®	1/8" x 1/8" x 1/8"	Square Notch	60 Sq. Ft.
3/8" – 1/2" thick Engineered wood to VERDEX®	3/16" x 1/4" x 1/2"	V-Notch	60 Sq. Ft.
9/16" thick or greater Engineered wood to VERDEX®	1/4" x 1/4" x 1/4"	Square Notch	30 Sq. Ft.
1/4" Engineered wood greater than 3" wide to VERDEX®	3/16" x 3/16" x 3/16"	Square Notch	35 Sq. Ft.

V – Bond Plus™

Application	Trowel Size	Trowel Type	Coverage* (Per Gallon)
VERDEX® to sub-floor	1/8" x 1/8" x 1/8"	Square Notch	80 Sq. Ft.
5/16" – 3/8" thick Solid Wood to VERDEX®	3/16" x 3/16" x 5/32"	V-Notch	50 Sq. Ft.
Greater than 3/8" up to 1/2" thick Solid wood to VERDEX®	1/4" x 1/4" x 1/8"	Square Notch	35 Sq. Ft.
4' x 4' Plywood to VERDEX®	1/4" x 1/4" x 1/4"	Square Notch	30 Sq. Ft.

*Coverage rates will vary from project to project. It is upon the installer to determine the quantity of 4 gallon buckets needed.